

DS-K1A340FX Face Recognition Terminal



The face recognition terminal supports take attendance via face, fingerprint and other credentials, which is mainly applied in buildings, enterprises, finance buildings, office buildings, security places, etc.

- Local time attendance
- 4.3-inch touch screen and 2 MP camera
- Face anti-spoofing; Face recognition distance: 0.3m to 1.5m
- Face recognition duration < 0.2 s/User; face recognition accuracy rate ≥ 99%
- Deep learning algorithm
- 1500 face capacity, 3000 fingerprint capacity, and 300,000 attendance records
- Multiple authentication modes
- Export registered face pictures and events from device via USB interface
- Manage, search and set device data after logging in the device locally
- Light supplement in the dark environment
- Supports English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)





Specification


| - Specification | |
|--------------------------------|--|
| System | |
| Operating system | Linux |
| Display | |
| Screen size | 4.3-inch |
| Operation method | Touch screen |
| Resolution | 480 × 272 |
| Video | |
| Lens | 2 |
| Resolution | 2 MP |
| Video standard | PAL (Default) and NTSC |
| Audio | |
| Tone quality | Built-in omnidirectional microphone |
| Volume adjustment | Support |
| Power output | 1 W |
| Interface | |
| USB | 1 |
| Capacity | |
| User capacity | 1500 |
| Face capacity | 1500 |
| Fingerprint capacity | 3000 |
| Event capacity | 300,000 attendance records |
| Authentication | |
| Face recognition distance | 0.3 m to 1.5 m |
| Face recognition accuracy rate | ≥ 99% |
| Face recognition duration | ≤ 0.2 s |
| General | |
| Working temperature | -10 °C to 40 °C (14 °F to 104 °F) |
| Dimensions | 118.4 mm × 118.4 mm × 21.8 mm (4.7" × 4.7" × 0.9") |
| Power supply method | 12 VDC |
| Application environment | Indoor |
| Language | English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil) |


Available Model

DS-K1A340FX



Dimension





Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400

T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T+7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com