SEMI-LOOK DOOR HIGH SPEED ALUMINIUM ROLL UP DOOR High Speed Door for interior & exterior applications

HIGH TECH ROLL UP FAST & FASHION DOOR | TECHNICAL SPECIFICATIONS

- Ideal solution in areas with high demand for logistics efficiency and heavy traffic
- Automatic super fast opening and closing
- Reduces leakage of heat and air, heat preservation
- Moveable shaft system
- No torsion spring, less need for spareparts, minimum cost
- 90% clear vision with polycarbon window
- One lamela close, one lamela polycarbon window system

Door Type		Roll-up
Use	Internal / External Door	Standard
Door Sizes	Max Width Max Height	5000 mm 5000 mm
Speed	Inverter Motion system to adjust different speeds, with progressive control of acceleration & deceleration during bral Opening Speed up to Closing Speed	2 m/s 0.7 m/s
Security Features	EN 13241-1	Standard
Resistance to Wind Load	EN 12424	up to Class 3
Door Leaf Material / Surface	Aluminium Anodized polycarbon windows RAL 9006 aluminium inside polycarbon	Standard Standard
Guide Material / Surface	Aluminium Anodized Painting in any RAL color	Standard Optional
Shaft / Operator Cover	Straight	Optional
Operator and Control (German brand)	Connecting Voltage 1-phase 3-phase	220V - 1 ph, N 380V - 3 ph, N
	Open-Stop-Close Button	Standard
	Protection Category (Operator / Control)	IP 54 / IP 65
	Emergency-OFF Button	Standard
	Closing Zone Monitoring Light Grille IP 67	Standard
	External Route Monitoring Photocell	Optional
	Door area Monitoring Radar Presence Detector	Optional
	Induction Loop	Optional
	Electronic Limit Switch	Standard
Emergency Opening	Crank Handle	Standard
	Chain	Optional
Standard Curtain Colours	White Similar to RAL 9016 Ivory Similar to RAL 1015 Light beige Brown Similar to RAL 8014 Green Similar to RAL 6005 Anthracite grey Similar to RAL 7016	