



### Product description

Model with basic equipment.

### Overview of Advantages

- Water-proof for use outdoors
- Protection rating IP54 for the electrical components
- Connecting cable 300 mm length
- Equipped with bipolar protective diodes
- Radius keep, FaFix®, adjustable by 3 mm
- Compatible with current mortise locks
- Striking plates with 2 position settings available
- Symmetrical design. DIN left/right as well as horizontal applicable

### Scope of delivery

- 1 piece electric strike

### Technical data

|                                |                         |
|--------------------------------|-------------------------|
| Adjustable keeper (FF, FaFix®) | Yes                     |
| Fail-locked                    | Yes                     |
| Bi-directional diode           | Yes                     |
| Break-in resistance            | 3750 N                  |
| Height                         | 66 mm                   |
| Width                          | 17,5 mm                 |
| Depth                          | 26 mm                   |
| FaFix® adjustment range        | 3 mm                    |
| Latch bolt engaging depth      | 5,5 mm                  |
| Operating temperature range    | -40 °C to +50 °C        |
| Installation position          | Vertical and horizontal |
| Load cycles for in-plant test  | 250000                  |

### Variants that can be ordered

| Order number | Description                           |
|--------------|---------------------------------------|
| 118W-----A71 | Without striking plate, 12-24V AC/DC  |
| 118W-----B71 | Without striking plate, 22-42 V AC/DC |
| 118W-----D11 | Without strike plate, 6-12 V AC/DC    |