



Product description

- OneSystem espagnolette N1910 for automatic locking of the passive leaf upwards or downwards for double-leaf doors. For use with OneSystem locks from the series N1050, N1550 and N16XX on the active leaf of double-leaf doors.

Characteristics

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 15 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Latch DIN left/right reversible without tools
- Closed lock case at the top and bottom
- Stainless steel faceplate
- Security fittings and oval roses can be screwed on through the lock
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

Technical data

Bolt throw	20 mm
Latch	DIN L/R (symmetrical face plate)
Standards	EN 12209
Distance	92 mm (prepared for Euro profile cylinder), 94 mm (prepared for Swiss round cylinder)
Backset	25, 30, 35, 40, 45 mm
Handle follower	8 mm
Front plate	U-shaped face plate: U6 x 24 mm Flat face plate: F3 x 20 mm, F3 x 24 mm, R3 x 20 mm, R3 x 24 mm
Material faceplate	Stainless steel

Variants that can be ordered

Order number	Front plate	Face plate length	Distance
N1910000XX*0007	F3 x 20 mm	270 mm	92 mm
N1910000XX*0008	F3 x 24 mm	270 mm	92 mm
N1910000XX*000A	U6 x 24 mm	270 mm	92 mm
N1910000XX*0003	R3 x 20 mm	270 mm	92 mm
N1910000XX*0004	R3 x 24 mm	270 mm	92 mm
N1910000XX*000D	F3 x 20 mm	320 mm	92 mm
N1910000XX*000E	F3 x 24 mm	320 mm	92 mm
N1910000XX*000F	U6 x 24 mm	320 mm	92 mm
N1910000XX*000B	R3 x 20 mm	320 mm	92 mm
N1910000XX*000C	R3 x 24 mm	320 mm	92 mm

