



### Product description

- OneSystem sash lock N1000 according to EN 12209 for single-leaf standard doors, product-specific environmental product declaration (EPD) according to EN 15804 with article-specific parameters / tested for 1,000,000 cycles and 300 kg door weight

### Characteristics

- Environmental product declaration (EPD) in accordance with EN 15804
- Tested for 1,000,000 cycles and 300 kg door weight
- Compliance with EN 12209
- Small rear backset 17 mm
- Continuous screw connection of fittings
- Suitable espagnolette integrated in the striking plate
- 20 mm bolt throw with a single rotation
- Also available as a fire protection version
- Closed lock case
- Latch DIN left/right reversible without tools
- Security fittings and oval roses can be screwed on through the lock
- Stainless steel faceplate
- Deadbolt with anti-tampering design
- Developed for Euro profile cylinder and Swiss round Profile cylinder

### Technical data

|                    |  |
|--------------------|--|
| Bolt throw         | 20 mm  |
| Latch              | DIN L/R (symmetrical face plate), DIN left or DIN right (asymmetrical face plate according to DIN 18251-1) |
| Standards          | EN 12209   |
| Distance           | 72 mm (prepared for Euro profile cylinder), 74 mm (prepared for Swiss round cylinder)                      |
| Backset            | 55, 60, 65, 80, 100 mm   |
| Handle follower    | 8 mm   |
| Front plate        | Flat face plate: R3 x 20 mm, R3 x 24 mm, R3 x 24   |
| Material faceplate | Stainless steel  |

### Variants that can be ordered

| Order number    | Front plate | Face plate length | Distance |
|-----------------|-------------|-------------------|----------|
| N100000081*000L | R3 x 20 mm  | 235 mm            | 72 mm    |
| N100000081*000K | R3 x 24 mm  | 235 mm            | 72 mm    |
| N100010081*000L | R3 x 20 mm  | 235 mm            | 72 mm    |
| N100010081*000K | R3 x 24 mm  | 235 mm            | 72 mm    |
| N100020081*000M | R3 x 20 mm  | 235 mm            | 72 mm    |
| N100030081*000M | R3 x 20 mm  | 235 mm            | 72 mm    |
| N100000088*000L | R3 x 20 mm  | 235 mm            | 74 mm    |
| N100000088*000K | R3 x 24 mm  | 235 mm            | 74 mm    |
| N100010088*000L | R3 x 24 mm  | 235 mm            | 74 mm    |
| N100010088*000K | R3 x 24 mm  | 235 mm            | 74 mm    |
| N100020088*000M | R3 x 20 mm  | 235 mm            | 74 mm    |
| N100030088*000M | R3 x 20 mm  | 235 mm            | 74 mm    |