

# ALUSPEED DOOR

## HIGH SPEED ALUMINIUM ROLL UP DOOR

High Speed Door for interior & exterior applications



### HIGH TECH ROLL UP FAST ALUMINIUM DOOR | TECHNICAL SPECIFICATIONS

- Ideal solution in areas with high demand for logistics efficiency and heavy traffic
- Automatic super fast opening and closing
- Reduces leakage of heat and air, heat preservation
- Moveable shaft system
- No torsion spring, less need for spareparts, minimum cost
- Patented rubber drive method

Door Type		Roll-up
Use	Internal / External Door	Standard
Door Sizes	Max Width	5500 mm
	Max Height	5500 mm
Speed	Inverter Motion system to adjust different speeds, with progressive control of acceleration & deceleration during braking	
	Opening Speed up to	3,0 m/s
	Closing Speed	0,7 m/s
Security Features	EN 13241-1	Standard
Resistance to Wind Load	EN 12424	Class 3
Door Leaf Material / Surface	Polyurethane filled RAL 9006 aluminium lamella	
Curtain	Aluminium	19.0 mm
Guide Material / Surface	Aluminium Anodized	Standard
	Painting in any RAL color	Optional
Shaft / Operator Cover	Straight	
Operator and Control (German brand)	Connecting Voltage	1-phase 3-phase
	Open-Stop-Close Button	
	Protection Category (Operator / Control)	
	Emergency-OFF Button	
	Closing Zone Monitoring	Light Grille IP 67
	External Route Monitoring	Photocell
	Door area Monitoring	Radar Presence Detector
		Induction Loop
	Electronic Limit Switch	
Emergency Opening	Crank Handle	
	Chain	
Standard Curtain Colours		