

DS-K1T671TMW Face Recognition Terminal



- Forced mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance will be failed
- Face mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance is valid
- 7-inch LCD touch screen, 2 Mega pixel wide-angle lens, built-in Mifare card reading module
- Face recognition distance (without face mask): 0.3 m to 3 m, Duration < 0.2 s/User, Accuracy rate ≥ 99%
- Max. 50,000 faces, Max. 50,000 cards
- Two-way audio with client software, indoor station, and main station
- Supports TCP/IP,Wi-Fi
- Configuration via the web client
- Supports ISAPI and ISUP5.0 protocol
- IP65





Specification

- Specification				
System				
Operation system	Linux			
Display				
Dimensions	7-inch			
Туре	LCD			
Operation method	Capacitive touch screen			
Video				
Pixel	2 MP			
Lens	2			
Audio				
Tone quality	Noise suppression and echo cancellation			
Network				
Wired network	10 M/100 M/1000 M self-adaptive			
Wi-Fi	Support			
Interface				
Network interface	1			
RS-485	1			
Wiegand	1			
Lock output	1			
Exit button	1			
Door contact input	1			
IO input	2			
IO output	1			
Power interface	2-pin			
TAMPER	2-pin 1			
USB	2			
Capacity	-			
Card capacity	50,000			
Face capacity				
Event capacity	50,000 100,000			
Authentication	100,000			
Card type	Mifare 1 card			
Card reading frequency	13.56 MHz			
Card reading frequency Card reading distance	0 to 5 cm			
Face recognition duration	< 0.2 s per person			
Face recognition accuracy rate	≥ 99%			
Face recognition distance	0.3 to 3 m (Without face mask)			
Function				
QR code recognition	Support			
Face anti-spoofing	Support			
Advertisement	Support			
Audio prompt	Support			




Time synchronization	Support			
General				
Power supply method	2 pin connecter			
Power supply	12 VDC/ 2 A			
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)			
Working humidity	10 to 90% (No condensing)			
Dimensions	239 mm × 116.5 mm × 33 mm (9.4" × 4.6" × 1.3")			
Protective level	IP65			
Installation	Wall mounting			
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)			
Platform	Hik-ProConnect and HikCentral Professional			

Available Model

DS-K1T607TMW

Dimension



Without Fingerprint Module



Accessory

Optional

DS-KAB671-B Stand Stick	DS-KAB671F Fingerprint Module	DS-KAB671-P1	DS-KAB671-S Protective Shield

Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400

T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com