

DS-K1T801 Series

Access Control Terminal

AVAILABLE MODELS

- DS-K1T801E (EM Card Only)
- DS-K1T801M (M1 Card Only)



MAIN FEATURES

- 32-bit processor
- Stand-alone operation management settings
- Max. 3000 card number settings
- Supports authentication method of card and card & password
- Opens door via card password if the authentication method is card
- Adds up to 3000 card passwords
- Supports exit button
- Supports ID card, and ID card number reading (DS-K1T801E)
- Supports Mifare card, Mifare card number reading (DS-K1T801M)
- Watchdog design
- Data can be permanently saved after power-off

SPECIFICATIONS

Parameters	Model	DS-K1T801E	DS-K1T801M
Processor		32bit	
Storage		Storage for 3000 Legal Card Information	
Card type		EM Card	Mifare Card
Input interface		Exit Button × 1, Door Sensor × 1	
Output interface		Doorbell × 1, E-lock Output × 1	
Key board		13 Keys (0-9, *, #, Doorbell)	
LED Indicator		Power/Status	
Voice prompt		Beeper	
Working voltage		12V DC	
Working current		0.17A (without Load)	
Working Temperature		-20°C to 65°C (-4° F to 149° F)	
Working Humidity		10% to 90% (No Condensing)	
Dimension		126.5(L)mm × 94.5(W)mm × 24(H)mm (4.98" × 3.72" × 0.94")	